

CLEAR VINYL - SUPERCLEAR™ 1600, 2000, 3000, 4000, 8000



Our **SUPERCLEAR™ Clear Vinyl Fabrics** combine **strength and durability**, making them ideal for a wide range of applications. Engineered for **superior performance**, these crystal-clear fabrics feature a low-shrinkage formula—averaging just 3.0%* — to help **maximize material yield** for your projects. They are also **ultraviolet (UV), anti-mildew, and fire-retardant** treated**.

FABRIC SPECIFICATIONS

SUPERCLEAR™ 1600

Weight	16 gauge Clear
Unit Width & Length	54, 61 in. - 50 yd. rolls
Composition	Unsupported Polyvinyl Chloride
Temperature Resistance	-15°C ~ 50°C, -5°F ~ 122°F

SUPERCLEAR™ 2000

Weight	20 gauge Clear
Unit Width & Length	54, 61, 72 in. - 50 yd. rolls
Composition	Unsupported Polyvinyl Chloride
Temperature Resistance	-15°C ~ 50°C, -5°F ~ 122°F

SUPERCLEAR™ 3000

Weight	30 gauge Clear
Unit Width & Length	61, 72 in. - 30 yd. rolls
Composition	Unsupported Polyvinyl Chloride
Temperature Resistance	-20°C ~ 50°C, -4°F ~ 122°F

SUPERCLEAR™ 4000

Weight	40 gauge Clear
Unit Width & Length	61 in. - 30 yd. rolls
Composition	Unsupported Polyvinyl Chloride
Temperature Resistance	-20°C ~ 50°C, -4°F ~ 122°F

SUPERCLEAR™ 8000

Weight	80 gauge Clear
Unit Width & Length	61 in. - 10 yd. rolls
Composition	Unsupported Polyvinyl Chloride
Temperature Resistance	-20°C ~ 50°C, -4°F ~ 122°F



- This product has a shrink rate of 3%, please factor this into your manufacturing process.

** F/R Treatment: California Fire Marshal, NFPA 701

CONTACT US TODAY!

(888) 727-7050 | sales@kedersolutions.com | kedersolutions.com

